/ Descriptions

TO-92 PNP Silicon PNP transistor in a TO-92 Plastic Package.

/ Features

VCE(sat) , ,h_{FE}


Low saturation voltage, excellent h_{FE} linearity and high h_{FE}.

/ Applications

3 , ,

Output stage of 3 watts audio amplifier, regulator, DC-DC converter and relay driver.

/ EquivaTD0n30cup//3-4.0m)-t5.7( )]TETf77 0B2 0495 rg57434 68.84824 18ref62434 68.16 469






PIN1 Base PIN 2 Collector PIN 3 Emitter


/ hFE Classifications & Marking

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-40	V
Collector to Emitter Voltage	V_{CEO}	-30	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-3.0	A
Collector Power Dissipation	P_C	1.0	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	V_{CB}=-30V I_E=0			-1.0	μA
Emitter Cut-Off Current	I_{EBO}	V_{EB}=-3.0V I_C=0			-1.0	μA
DC Current Gain	$h_{FE(1)}$	V_{CE}=-2.0V I_C=-1.0A	60	160	400	
	$h_{FE(2)}$	V_{CE}=-2.0V I_C=-20mA	30	220		
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=-2.0A I_B=-0.2A		-0.3	-0.5	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	I_C= - 2 . 0 A I				


/ Electrical Characteristic Curve






/ Package Dimensions

TO-92 Unit: mm



/ Marking Instructions



BR:

B772S


R: h_{FE}

****

Note:

BR:	Company Code.
B772S:	Product Type.
R:	h_{FE} Classifications Symbol
****:	Lot No. Code,code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



				Note:
1	25	150	60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2	255±5		5±0.5sec;	2.Peak Temp.:255±5 , Duration:5±0.5sec.
3		2 10	/sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270±5	10±1 sec.	Temp:270±5	Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension		(unit mm3)

/ AMMO

Package Type	Units					Dimension	(unit mm3)

/ Notices