
BRCL3130DZZ MOSFET
MOSFET


BRCL3130DZZ DFN2×2-8L

- 16mΩ MOSFET
- DFN2×2-8L
-
-
- 3.5 μA
- 0.6 μA
-

Single lithium ion rechargeable battery pack, single lithium polymer rechargeable battery pack.



R1 1kΩ -2kΩ , C1 0-1uF
R1 1K



Pin Number	Pin Name	Pin Description
1	VDD	
2,3,4	GND	
5,6,7,8	VM	
EPAD	GND	

/Parameter	/Symbol	/Value	/Unit
V_{DD} input pin voltage	V_{IN}	-0.3 to +8	V
V_{VM} input pin voltage	V_{VM}	-8 to +10	V
Maximum Junction Temperature	T_J	-40 to +145	
Storage Temperature	T_{stg}	-55 to +145	
ESD HBM Mode	ESD	± 4000	V


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Supply Voltage	V_{DD}		0		6	V
Charger input voltage	V_M		-6		6	V
Overcharge Detection Voltage	V_{OCV}		4.25	4.3	4.35	V
Overcharge Release Voltage	V_{OCR}		4.04	4.10	4.16	V
Overdischarge Detection Voltage	V_{ODV}		2.30	2.40	2.50	V
Overdischarge Release Voltage	V_{ODR}		2.90	3.00	3.10	V
Overdischarge Current Detection	I_{OCI}		9	11.5	14	A
Load Short-Circuiting Detection	I_{SHORT}		15	25	35	A
Overcharge Current Detection	I_{CHA}		7	10	13	A
Current Consumption in Normal Operation	I_{OPE}	V_M=0V		3.5	7	μA
Current Consumption in Dormancy	I_{PDN}	V_{DD}=1.8V		0.6	1.5	μA
Internal pull-up current	I_{PU}			14		μA
Internal pull-down current	I_{PD}	V_M=1V		14		μA
Equivalent FET on Resistance	R_{DS}	I_{VM}=1A	12.5	16	18	mΩ

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Over-temperature protection	OTP			145		
Over-temperature protection release temperature	OTPR			120		
Overcharge Voltage Detection Delay Time	T_{OCV}			100		ms
Overdischarge Voltage Detection Delay Time	T_{ODV}			100		ms
Overdischarge Current1 Detection Delay Time	T_{IOV1}			8		ms
Overdischarge Current2 Detection Delay Time	T_{IOV2}			2		ms
Load Short-Circuiting Detection Delay Time	T_{SHORT}			150		μs

* (OTP) OTPR

*

/



/

BRCL3130DZZ

MOSFET 16mΩ

BRCL3130DZZ

/

/

(VOCV)

(TOCV) BRCL3130DZZ MOSFET

(TOCV)

1 VM (VCHA) (VOCR)

2 (Vocv)

/ Overcharge Current Condition

ICHA (TOCI) MOSFET

BRCL3130DZZ

/

(VODV)

(TODV) BRCL3130DZZ

MOSFET VDD 2.3V ( )

(IPDN). VDD 2.4V ( )

(VODR) BRCL3130DZZ

/

VM

VM

/

VM (VSHORT)

TSHORT VM

/

VM (V_{CHA})


(V_{ODV}) BRCL3130DZZ

0V /

0V 2.3s ט ז Ḣ ס ז u ׳ ļ ķ %


/

→ → / → →



Charge
Dischage
VOCV
VOCR
VODR
VDD
Vshort
GND
VCHA
tODV
tODV
Charge Current
0
Discharge Current
ODV State
ODV State

/

→ / →


Charge
Dischage
VOCV
VOCR
VODR
VODV
GND
Charge
Current
0
Discharge

DFN2×2-8L-0.75 Unit:mm



Dimensions

Rev.00 202012



3130D

****

Rev.B Nov.-2025