/ Descriptions

SOP-8 P MOS
P-Channel Enhancement Mode Field Effect Transistor in a SOP-8 Plastic Package.


/ Features

V_{DS}(V)=-30V I_D=-5.0A
$R_{DS(ON)}$ <65mΩ(V_{GS}=-10V)
$R_{DS(ON)}$ <75mΩ(V_{GS}=-4.5V)


/ Applications

Power Management in Notebook computer, Portable Equipment and Battery powered systems and this device is suitable for use as a load switch or in PWM applications.

/ Equivalent Circuit



/ Pinning



PIN1	S2	PIN 2	G2	PIN 3	S1	PIN 4	G1
PIN 5	D1	PIN 6	D1	PIN 7	D2	PIN 8	D2

/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±12	V
Continuous Drain Current[A]	I_D (T_a=25°C)	-5.0	A
	I_D (T_a=70°C)	-4.2	A
Pulsed Drain Current[B]	I_{DM}	-20	A
Power Dissipation for Single Operation[A]	P_D (T_a=25)	2.0	W
	P_D (T_a=70)	1.4	W
Junction and Storage Temperature Range	T_j,T_{stg}	-55 +150	
Thermal Resistance-Junction to Ambient[A]	$R_{\theta JA}$ t 10s	62.5	/W
	$R_{\theta JA}$	110	/W
Maximum Junction-to-Lead[C]	$R_{\theta JL}$	40	/W

Note:

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.


D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.


Â 4 ›

Parameter	Symbol	Test Conditions

/ Electrical Characteristic Curve



/ Electrical Characteristic Curve



/ Package Dimensions



BRCS4803SC BRC( )Tj 1 Tf12 0 -43.0914 -69.394BRCS4http://www.fsbrec.com/03S7(