/ Descriptions

WR0553I ṂṂ Ƭ QSQ ÆṀ ч s ‖ ㄱ Silicon NPN transistor in a TO-220F Plastic Package.

/ Features

kIH ㅓ ó Ḅ/лъ NWE469; Ӣ ´


Good Linearity of h_{FE}, complementary pair with KTB1368.

/ Applications


ᵹ ˇ ѽ ᶻ

General Purpose Application.

/ Equivalent Circuit



/ Pinning




PIN1 χ Base PIN 2 χ Collector PIN 3 χ Emitter

/ h_{FE} Classifications & Marking


h_{FE} Classifications Symbol	R	O	Y
h_{FE} Range	40~80	70~140	120~240

v ̈Ω Parameter	ϒ N Symbol	̈Ω Ö Rating	D Ђ Unit
Collector to Base Voltage	V_{CBO}	80	V


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



◡ ˝ χ	
EU χ	⊮ ϛ ᴎ Γϑ
G5393 χ	⊮ ϛ ᴺ Γϑ
U=	⊮ ⁶ Ҡ Γϑ
---- χ	⊮ ⊦ ꜰ ή ᴺ Γϑ ι ₡ ⊦ ꜰ ή ᴺ Ψ ϼ


Note:

BR: Company Code.

D2060: Product Type.

R: h_{FE} Classifications Symbol.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ɬ ı ˋH ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ɬ ı ˋH ڑ ˋY ﾊ ㎛ 5 ° 0.5sec;

3 ì ˙ ﾘ ˛ ɔ ෯ ỷ ㎛ 2 Ḱ 10 ɬ /sec.

Note:

1.Preheating:25~150 ɬ , Time:60~90sec.

2.Peak Temp.:255 ° 5 ɬ , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ɬ /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ɬ ˋH ڑ χ 10 ° 1 sec. Temp:270±5 Time:10±1 sec

/ Packaging SPEC.

ˈ Ω ţ ﾔ Ь / BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

˛ ﾘ ﾔ Ь / TUBE

Package Type	Units					Dimension (unit mm3)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-220F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices