TO-553 Ь

Schottky Barrier Diode in a TO-220 Plastic Package.

Ң ∪ Ң ǎ ≍ ظΦ

Low forward voltage drop,low poer losses,High efficiency operation.


≍ إ گ ∧ OR-ing GF-GF ج

For use in high frequency inverters, switching

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RM} V_{RSM} V_{DC}	100	V
RMS Reverse Voltage	V_{RMS}	70	V
Average Rectified Forward Current	$I_{F(AV)}$	2×20	A
Non Repetitive Peak Surge Current	I_{FSM}	300	A
Thermal Resistance Junction to Case	$R_{\theta Jc}$	2.8	/W
Junction and Storage Temperature Range	T_j T_{stg}	-40 +150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_{BR}	I_R=1mA(Ta=25)	100			V
Forward Voltage	V_F	I_F =5A(Ta=25)		0.45		V
		I_F =10A(Ta=25)		0.54		V
		I_F =20A(Ta=25)		0.67	0.75	V
		I_F =5A(Ta=125)		0.38		V
		I_F =10A(Ta=125)		0.49		V
		I_F =20A(Ta=125)		0.62	0.65	V
Instantaneous Reverse Current	I_R Note 1	V_R=100V(Ta=25)		30	200	μA
		V_R=100V(Ta=125)				

ł. Ļ‘Ω / Marking Instructions



ِ

ER и

LV43433 N


FT: Աĥ ل

**** N ₲ N

Note:

BR:	Company Code
LV40100	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

↓ ș ╕ẅ´E ᛋ ƒ (ᾠ ᴈ) / Temperature Profile for Dip Soldering(Pb-Free)



ب		Note:
1	ἶ 25 150 ڑ 60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2	255±5 ڑ ᛋ 5±0.5sec;	2.Peak Temp.:255±5 , Duration:5±0.5sec.
3	ᵴ 2 10 /sec.	3. Cooling Speed: 2~10 /sec.

ᛋ ŭ ɋ ¯ Y Ţ / Resistance to Soldering Heat Test Conditions

270±5	ڑ 10±1 sec.	Temp.:270±5	Time:10±1 sec

ɒ Ŀ ᦉ — / Packaging SPEC.

Ŀ / BULK

Package Type	Units	Dimension	(unit mm^3)