

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	180	V
Collector to Emitter Voltage	V_{CEO}	160	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current - Continuous	I_C	600	mA
Base Current - Continuous	I_B	300	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	V_{CB}=180V I_E=0			0.1	A
Emitter to Base Current	I_{EBO}	V_{EB}=6.0V I_C=0			0.1	A

≠ Ǝ ÃʹE ᴎ ʃ






ᵘ ĖÒĻ ʃ



ł. ŀ Ω



H

G1

A h_{FE}


Note:

H: Company Code.

G1 Product Type.

A h_{FE} Classifications Symbol

Wh p shudwxuh Suriloh iru LU Uhiorz Vroghulqj+Se0luhh,



Note:

1 25 150 60 90sec;

1.Preheating:25~150 , Time:60~90sec.

2 245±5 5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3 2 10 /sec.

3. Cooling Speed: 2~10 /sec.

٠ ü qÍ`Y Ţ

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

ɒ Ŀ ɾ—

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

ä ѵ ŗ Ѽ