



Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	200	V
RMS Voltage	V_{RMS}	140	V
DC Blocking Voltage	V_{DC}	200	V
Average Forward Current	I_F	2 × 8	A
Non Repetitive Peak Surge Current	I_{FSM}	120	A


IF - TA
20
15
10
5
0
IF(A)
25
50
75
100
125
150
175
TC


IFSM
6
100
75
50
25
0






BR	И		
MXR4653		N	
CW:			
****		N	N

Note:

BR:	Company Code
MXR4653	Product Type.
CW:	Internal Structure
****:	Lot No. Code, code change with Lot No.



		Note:	
1	25 150 60 90sec;	1.Preheating:25~150 , Time:60~90sec.	
2	255±5 5±0.5sec;	2.Peak Temp.:255±5 , Duration:5±0.5sec.	
3	2 10 /sec.	3. Cooling Speed: 2~10 /sec.	

270±5	10±1 sec.	Temp.:270±5	Time:10±1 sec

/ BULK

Package Type	Units					Dimension (unit mm³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type	Units					Dimension (unit mm³)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180