/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.

/ Features


,

Low collector saturation voltage, high DC current gain, large current capability..

/ Applications

Low voltage large current drivers.

/ Equivalent Circuit






PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	15	V
Emitter to Base Voltage	V_{EBO}	6.5	V

ColCur(Rat[Denol)8ng)-18e V

/ Package Dimensions



/ Marking Instructions



H


123

Note:

H: Company Code.

123: Product Type Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



					Note:	
1	25	150		60 90sec;	1.Preheating:25~150	, Time:60~90sec.
2	245±5			5±0.5sec;	2.Peak Temp.:245±5	, Duration:5±0.5sec.
3			2 10	/sec.	3. Cooling Speed: 2~10	/sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱

/ Notices